

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. **(currently amended)** A semi-automatic construction method for a knowledge base of an encyclopedia question answering system, the method comprising the steps of:

(a) ~~designing~~ constructing a structure of the knowledge base with a plurality of templates for each entry of an encyclopedia and a plurality attributes related to each of the templates;

(b) automatically extracting structured information, including ~~the entry~~, an attribute name and associated attribute values, from summary information of the entry in the encyclopedia;

(c) automatically extracting unstructured information, including an attribute name and associated attribute values, ~~of the entry~~ from a body of the entry in the encyclopedia; and

(d) storing the automatically extracted structured information and [[the]] unstructured information in the corresponding templates and attributes of the knowledge base according to the entry.

2. (original) The method of claim 1, wherein in the step (a), the structure of the knowledge base is constructed with common attribute templates of a common attribute shared in categories of the encyclopedia and individual attribute templates of a specific attribute of an individual category of the encyclopedia, for each entry.

3. **(currently amended)** The method of claim 1, wherein in the step (a), attributes

having similar meaning are managed as a representative attribute integrally and detailed meanings of the attributes are grouped and defined in separate subgroup fields.

4. **(currently amended)** The method of claim 1, wherein the step (b) comprises the steps of:

- (b-1) recognizing a patterned format of the summary information of each entry; and
- (b-2) extracting the ~~entry~~, the attribute name and [[the]] associated attribute values based on the recognized patterned format.

5. **(currently amended)** The method of claim 4, wherein the step (b-2) comprises the steps of:

- (b-2-i) extracting ~~the entry and~~ the attribute name through the recognized patterned format of the summary information of each entry;
- (b-2-ii) ascertaining whether the extracted attribute name belongs to a valid attribute in an attribute list of the templates of the knowledge base; and
- (b-2-iii) extracting the corresponding attribute value from the summary information only if the extracted attribute name belongs to the valid attribute in the attribute list of the templates of the knowledge base, ~~extracting the corresponding attribute value~~.

6. **(original)** The method of claim 4, wherein the step (b) further comprises the steps of:

- (b-3) if the extracted attribute name has a plurality of attribute values, extracting each of the plurality of attribute values separately by marked identifiers.

7. **(currently amended)** The method of claim 1, wherein the step (c) comprises the steps of:

- (c-1) converting each sentence of an illustrative corpus into a token string, recognizing

dependence relation of an attribute tagging token, generating learning data, and learning the learning data through a predetermined stochastic model; and

(c-2) converting each sentence of the body of each entry of the encyclopedia into [[the]] a token string, recognizing dependence relation of an extraction object tokens, and applying a learning result and the stochastic model of step (c-1) to a recognition result, thereby finding and extracting the attribute name and the attribute value of each extraction object token.

8. **(currently amended)** The method of claim 7, wherein the step (c-1) comprises the steps of:

(c-1-i) performing morpheme parsing on the illustrative corpus ~~of the encyclopedia~~, which is tagged with an object name and an attribute, and recognizing a word-phrase unit token string according to sentences for each sentence of the illustrative corpus;

(c-1-ii) applying a predetermined dependence rule to a token tagged with an attribute value in the token string, thereby recognizing dependence relation between a governor and a dependent for the object token; and

(c-1-iii) generating the learning data by using the governor and the dependent of each object token as ~~contexts~~ context, and storing the learning result in the stochastic model.

9. **(currently amended)** The method of claim 7, wherein the step (c-2) comprises the steps of:

(c-2-i) performing the morpheme parsing and object name recognition on the body of each entry of the encyclopedia, and converting each sentence of the body into [[the]] a word-phrase unit token string;

(c-2-ii) designating a token of the token string as an extraction object token, the token of the token string having object name or full morpheme as a noun;

(c-2-iii) applying a predetermined dependence rule to each of the designated extraction object tokens, and recognizing a context token of the governor and the dependent; and

(c-2-iv) applying the extraction object token and the context token to the learning result and the stochastic model, grouping attribute types of the extraction object tokens, and extracting the attribute type of the extraction object tokens that have highest probabilities with the attribute names and the attribute values of the extraction object tokens.

10. (original) The method of claim 8, wherein, in the dependence rule used to recognize the dependence relation, the governor is a verb phrase nearest to the dependent if the dependent is any one selected from the group consisting of a subjective case, an objective case and an adverbial case, and the governor is a noun nearest to the dependent if the dependent is any one selected from the group consisting of an adnominal phrase and an adnominal clause.

11. (original) The method of claim 8, wherein in the dependence rule used to recognize the dependence relation, in case of neighboring nouns and/or object names, a preceding noun or a preceding object name is a dependent and a following noun or a following object name is a governor.

12. (original) The method of claim 8, wherein in the dependence rule used to recognize the dependence relation, when tokens around an object name or nouns are symbols, a verb phrase of a sentence is a governor.

13. (original) The method of claim 7, wherein a maximum entropy model is used as the stochastic model.

14. **(currently amended)** The method of claim 1, wherein the step (d) comprises the steps of:

(d-1) constructing the knowledge base with the attribute name and the attribute values extracted in the step (b); and

Serial No. 10/828,281

(d-2) additionally storing the attribute name and the attribute values extracted as the unstructured information in the knowledge base according to existence of the same attribute value of the entry.